

4BAR Flex Q ILS

- Complete wash lighting solution fitted with high-intensity, quad-color (RGBA) LEDs
- ILS compatibility for use in the ILS ecosystem
- Mounts to most tripods or speaker stands, without the need for additional clamps, using the pass-through hole
- Generate a broad spectrum of colors and achieve natural-looking color temperatures with punchy amber LEDs
- D-Fi™ USB compatibility for wireless master/slave or DMX control
- Create the ultimate light show by mounting up to 4 additional fixtures to the top of the 4Bar Flex Q
- Provide electricity to the additional lights by using the built-in Edison plugs
- Maximize setup possibilities and configurations with 2 included L-brackets
- Easily set up and tear down in minutes with the included carrying bag
- Multiple control options include standalone, DMX mode, wireless footswitch or the IRC-6 remote
- Safely mounts to truss using built-in bolts

Specifications

- DMX Channels: 4, 6 or 19
- DMX Connectors: 3-pin XLR
- Light Source: 28 LEDs (quad-color RGBA) 3.5 W, (1.3 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 20 Hz
- Beam Angle: 14°
- Field Angle: 23°
- Illuminance: 2,353 lux @ 2 m (per pod)
- Operating Frequency (D-Fi): 2.412 to 2.484 GHz
- Operating Frequency (foot switch): 433 MHz
- Max Unobstructed Distance (foot switch): 100 ft (30.5 m)
- Footswitch battery: 9 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 80 W, 1.2 A @ 120 V, 60 Hz
- Power and Current: 78 W, 0.6 A @ 230 V, 50 Hz
- Fits Tripod Sizes: 1.5 in (36.80 mm)
- Bracket Mounting Hole: M10 (1.5 mm pitch)
- Weight: 12.2 lb (5.5 kg)
- Weight (Controller): 1.2 lb (0.6 kg)
- Size: 45.7 x 2 x 12 in (1186 x 50.8 x 305 mm)
- Size (Controller): 16.5 x 5.2 x 1.5 in (419 x 132 x 38 mm)
- Included controller: IRC-6
- Optional controller: D-Fi USB
- Approvals: CE, RoHS, UKCA

