

## Key features:

- Reflex-loaded 15" low frequency loudspeaker
- Tough high excursion transducer with 4" voice coil
- Fibreglass enclosure
- Phoenix connector with link through for quick and reliable hook ups
- Marine-grade stainless steel fittings
- UV-resilient paint



The Air 15 is a reflex-loaded 15" fibreglass subwoofer with styling that compliments mid-high enclosures from both the Air and Cyclone series. Its large-scale output allows fully formed systems to be achieved in any environment.

Air 15's non-resonant fibreglass enclosure contributes to its impressive SPL and low frequency extension capabilities. Key features include an IP-55 rating made possible by 'ingress proof vent technology' and UV-resilient paint, allowing Air 15 to perform in both internal and external spaces requiring comprehensive coverage. Perfect for medium sized nightclubs and dance venues, larger bars, restaurants and beach clubs, retail settings, theme parks and marine based applications.

## Specifications

Frequency response	45 Hz - 160 Hz $\pm 3$ dB
Efficiency <sup>1</sup>	97 dB 1 W / 1 m
Nominal impedance	8 $\Omega$
Power handling <sup>2</sup>	500 W
Maximum output <sup>3</sup>	123 dB Cont, 129 dB Peak
Driver configuration	1 x 15" LF
Connectors	Phoenix connector with link out
Weight	29 kg (63.9 lbs)
Enclosure	Fibreglass composite
Mounting	T75 mounting bracket
Finish	Smooth cellulose

<sup>1</sup> Measured in half space <sup>2</sup> AES2 - 1984 compliant <sup>3</sup> Calculated

