Reversible Module

SDI Audio Embedder

XVVRM-AUDIO2SDI

— (**E**)embedder





The SDI Audio Embedder Reversible Module fits in the 8-Bay Reversible Rackmount Converter system.

heatrixx

The module can be inserted in the 8-Bay Frame in either direction, allowing the inputs/outputs to be positioned either at the front or the back of the unit depending on the application. There are no exposed PCBs as all modules are enclosed, and therefore protected against static shock, dust and general wear and tear. Gold-plated, redundant spring pins with magnetic retention deliver DC power to the modules, meaning no messy cabling and external power bricks are needed.

Specifications

Connections

Video Input Auto switching between 1 x 3G/HD/SD SDI

BNC & 1 x HDMI 1.4 type A with locking

system

2 x Balanced + 4dB XLR (analog) **Audio Input**

each with a 3-segment LED meter

Video Output 1 x 3G/HD/SD SDI BNC

Supported Signals

3G Format Support 1080p50, 1080p59.94, 1080p60

720p50, 720p59.94, 720p60, 1080i50, **HD Format Support**

1080i59.94, 1080i60, 1080p23.98,

1080PsF23.98, 1080p24, 1080PsF24, 1080p25,

1080PsF25, 1080p29.97, 1080PsF29.97,

1080p30, 1080PsF30

SD Format Support 525/23.98 NTSC, 525/29.97 NTSC.625/25 PAL

4:2:2 and 4:4:4 **SDI Video Sampling**

SDI Audio Sampling Sample rate of 48 kHz and 24 bit

YUV and RGB **SDI Color Space**

Automatically detects incoming signal format **SDI Auto Switching**

Embedding to SDI Channels 1 & 2

SMPTE Standards 425 M Level A & B, 424 M Level A, 292 M, 259 M

Physical Specifications

Height 121.5 mm (4.78 in)

Depth 225 mm (8.85 in)

Width 41 mm (1.61 in)

Weight 710g (1.56 lbs)

Alternate Form Factor Also available as a standalone converter

Environnemental Specifications

Relative Humidity 0% to 90% non-condensing

Operating Temperature 0-40 °C

Power Requirements

Reversible redundant power fed by XVVRF8 **Power Supply**

(8-Bay Rackmount Frame)

Power Consumption 20W

12VDC Voltage Range

In the Box

Theatrixx Reversible Module SDI Audio Embedder

Certifications & Compliance

This device complies with the following international standards



Ordering Information

XVVRM-AUDIO2SDI...... Theatrixx Reversible Module SDI Audio Embedder

XVVRF8 Theatrixx 8-Bay Reversible Frame

XVVRM-BLANK Theatrixx Blank Module