

COLORband PiX-M ILS

HIGHLIGHTS

- Moving strip light creates dynamic sweeping effects and functions as a pixel mapping effect, blinder or wall-washer
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- ILS compatibility for use in the ILS ecosystem
- D-Fi USB compatibility for wireless master/slave or DMX control
- Flexible control options with onboard 3 and 5-pin DMX connectors
- Angle the light where it's needed using the built-in motors
- Create eye-catching animations and video effects with individual LED control
- powerCON®-compatible power input/output connections for power linking
- Fits best in the CHS-60 VIP Gear Bag

SPECIFICATIONS



- DMX Channels : 5, 6, 8, 10, 17, 32, or 36
- DMX Connectors : 3- and 5-pin XLR
- Light Source : 10 LEDs (tri-color RGB) 6 W, (2A), 50,000 hours life expectancy
- Strobe Rate : 0 to 29 Hz
- Beam Angle : 15°
- Field Angle : 27° 7,441 lux @ 2 m
- Illuminance : 7,441 lux @ 2 m
- Power Linking : 12 units @ 120 V; 20 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
 - 86 W, 1.2 A @ 120 V, 60 Hz
 - 84 W, 0.7 A @ 230 V, 50 Hz
- Weight : 8.2 lb. (3.7 kg)
- Size : 31 x 2.6 x 4.8 in (785 x 67 x 123 mm)
- Approvals : CE, UKCA, ROHS
- Tilt : 245°
- Bracket Mounting Hole : 13 mm
- Optional Controllers : RFC, RFC-XL

WHAT'S INCLUDED

- COLORband PiX-M ILS
- Power cord
- Quick Reference Guide