




COMPACT C 32 WP

TWO-WAY PROFESSIONAL SPEAKER



Description

COMPACT C 32 WP is a multipurpose two-way point source speaker, suitable for a wide range of near and mid-distance applications. The combination of a 3" neodymium compression driver, a 12" neodymium woofer, and a constant directivity rotatable waveguide produces coherent 100° x 50° coverage for the listening area with high SPL, and distortion-free sound. The sleek and lightweight wood cabinet uses a special polyurea coating and a robust powder-coated grille with protective foam. Optional mounting accessories allow for wall or ceiling installation. Suitable for outdoor applications. EN 54-24:2008 technical data available in the user manual.

Features

- › 600 W power handling (RMS)
- › 137 dB max SPL
- › 54 ÷ 20000 Hz frequency range
- › 100° x 50° constant directivity coverage angle
- › 1 x 12" high power neodymium woofer
- › 1 x 3.0" v.c. neodymium compression driver
- › High quality birch plywood cabinet
- › Steel grille with water-repellent protection
- › Installation points available on top, bottom, rear and side panels
- › 2 x eco|mate IP 67 connectors

Part Number

13000911 COMPACT C 32 WP 8ohm


Black - RAL 9005 EAN 8024530022822



COMPACT C 32 WP

TWO-WAY PROFESSIONAL SPEAKER

Line Art 2D



TECHNICAL SPECIFICATIONS

| | | |
|----------------------------------|---|--|
| Acoustical specifications | Frequency Response (-10dB) | 54 Hz ÷ 20000 Hz |
| | Max SPL @ 1m | 137 dB |
| | Horizontal coverage angle | 100° |
| | Vertical coverage angle | 50° |
| | Directivity index Q | 10 |
| | System Sensitivity | 97 dB |
| Power section | Amplification | Full Range |
| | Nominal Impedance | 8 ohm |
| | Power Handling | 600 W RMS |
| | Peak Power Handling | 2400 W PEAK |
| | Protections | Dynamic Active Mosfet |
| | Crossover Frequencies | 1100 Hz |
| Recommended Amplifiers | XPS 16K, XPS 16KD, QPS 10K, QPS 6.0K, IPS 5.0K, IPS 2.5K, IPS 1.5K, DMA 504 | |
| Transducers | Compression Driver | 1 x 1.4" neo, 3.0" v.c |
| | Woofer | 1 x 12" neo, 3.5" v.c |
| Input/Output section | Input connectors | Amphenol eco/mat IP 67 |
| | Output connectors | Amphenol eco/mat IP 67 |
| Standard compliance | IP protection grade | IP 33C |
| | Safety agency | CE compliant |
| | EN54-24 certified | Yes |
| | CPR number | 0068-CPR-234/2025 |
| Physical specifications | Cabinet/Case Material | Birch plywood |
| | Hardware | 4 x M8, 14 x M10 |
| | Grille | Steel grille with water-repellent protection |
| | Color | Black - RAL 9005 |
| Size / Weight | Height | 620 mm / 24.41 inches |
| | Width | 361.8 mm / 14.24 inches |
| | Depth | 404 mm / 15.91 inches |
| | Weight | 23.5 kg / 51.81 lbs |



COMPACT C 32 WP

TWO-WAY PROFESSIONAL SPEAKER

Rigging / Mounting

ACCESSORIES

HORIZONTAL BRACKETS

13360703 HBR60703

Black - RAL 9005 EAN 8024530023843

VERTICAL BRACKETS

13360533 V-BR 002

Black - RAL 9005 EAN 8024530021320

WALL MOUNT BRACKETS

13360539 WM-BR 001

Black - RAL 9005 EAN 8024530021344

Upgrade Kits

HORN KIT

13360505 HN-KIT COMPACT C 32 C 45

Black EAN 8024530020019