



D-Fi Hub

D-Fi Hub is a compact, easy-to-use DMX unit that functions as either a transmitter or receiver. For more stable communication between units, it operates on a 2.4 GHz frequency range and includes an “auto” function which automatically finds the best frequency and syncs the units effortlessly. You can wirelessly synchronize an unlimited number of D-Fi-ready fixtures simultaneously, and operate them using the simple navigation on the OLED digital display.



Highlights

- Compact, easy-to-use wireless D-Fi transmitter and receiver in a single unit
- Wirelessly synchronize an unlimited number of D-Fi-ready fixtures and receivers simultaneously
- Built-in options include manual or automatic channel selection
- Simple navigation and text readout using the OLED digital display
- Mounting options include built-in hook and loop fastener strap, keyhole mounting holes, M10 and M12 threaded holes for direct mounting to truss
- Fully FCC/RTTE compliant

Specifications

- DMX Connectors: 3-pin XLR
- Input Voltage: 9 VDC, 500 mA (external power supply: 100 to 240 VAC, 50/60 Hz)
- Power and Current: 4 W, 0.1 A @ 120 V, 60 Hz
4 W, 0.1 A @ 230 V, 50 Hz
- Weight: 1.2 lb (0.6 kg)
- Size: 4 x 3.2 x 1.6 in (102 x 82 x 41 mm)
- Approvals: CE, FCC
- Max Unobstructed Distance:: 656 ft (200 m)