

The ER-2930W is a shoulder megaphone having facilities of EXT. mic input, an AUX input, a DC power input, a battery meter whistle sound. It can be mounted to the optional ST-16A speaker stand. The newly developed poly-imide diaphragm is employed to ensure high sound quality.



Order no: ER-2930W EU  
Alternative products: ER-2215, ER-2215W,  
ER-2230W

### Specifications

|                        |  |
|------------------------|--|
| Power source           | 10 x 1,5 V (R 20P)   |
| Rated output           | 30 W (45 W max.)   |
| Battery life           | 17 h   |
| Battery life on signal | 90 min   |
| Ext. MIC Input         | 600 Ω, unbalanced, ø6.6 phone jack, stereo plug acceptable, volume control |
| Signals                | Whistle  |
| Audible range          | 800 m (Whistle 1,000 m)  |
| Dimensions (W x H x D) | x 512  |
| Dimensions (ø x D)     | 351 x 512 mm   |
| Finish                 | Aluminium, ABS resin, die-cast, light grey (RAL 7035 or equivalent), grey  |
| Operating temperature  | -10 °C to +40 °C   |

### Appearance

<Note on the audible range and battery life>

1. The indications of the audible range and battery life are based on the JEITA Standard (\*2).
2. Audible Range presumes that the megaphone employs new batteries and is used on a quiet street.  
It varies depending on such conditions as battery consumption, ambient noise, wind direction and obstacles.
3. Battery Life assumes that megaphone is used for 30 minutes a day.

