




Exterior PixLine 10

The Exterior PixLine 10 is a linear LED video fixture for media facades and creative installations. The Exterior PixLine 10 can be combined with a wide variety of lenses and diffusers for the right look for every application. The Exterior PixLine 10 is driven by the Martin P3 System Controller family for easy setup and video display, and it is also backwards compatible with DMX. The fixtures can be fully customized in terms of length and color to match every installation requirement, while the power source is hidden.

GALLERY



Wide variety of pixel pitch, lens and diffusers options for flexibility of look

Fully outdoor-rated and customizable in terms of length and color

Easy setup and cabling for clean installation

FEATURES

- 10 mm pixel pitch
- 250 cd per meter calibrated
- 160 lumen per foot calibrated
- High-quality 16-bit per color image processing technology
- Pixel-level brightness and color calibration for optimal image quality
- P3/DMX controllable (automatic protocol detection)
- Intuitive mapping and addressing via P3 System Controller
- Combined power/data input (single cable for power and data input)
- Supported by integrated power and data processor (P3 PowerPort 1500 or P3 PowerPort 1000 IP) and simple cabling system
- Available in standard length of 1280 mm and 320 mm (customized lengths also available)

TECHNICAL SPECIFICATIONS

Physical

Length: Available in 320 mm (12.6 in.) and 1280 mm (50.4 in.) length versions

Custom lengths are available to special order on project basis as follows:

Minimum custom length: 300 mm (11.9 in.)

Maximum custom length: 2000 mm (78.8 in.)

Custom length increments: 20 mm (0.8 in.)

Width: 27 mm (1.1 in.)

Height with flat diffuser / clear front: 32 mm (1.3 in.)

Height with flat diffuser / clear front in mounting profile: 74 mm (3.0 in.)

Height with asymmetric wallwasher lens: 42 mm (1.7 in.)

Height with asymmetric wallwasher lens in mounting profile: 84 mm (3.4 in.)

Height with round diffuser: 42 mm (1.7 in.)

Height with round diffuser in mounting profile: 84 mm (3.4 in.)

Weight: 1.2 kg / m (0.9 lbs. per foot)

Control and Programming

Control options: Martin P3™ System Controller via Martin P3™ PowerPort 1500 /

Martin P3™ PowerPort 1000 IP, and/or DMX

Protocol detection: Automatic

Control modes: RGB, basic, segment and pixel-level

DMX channels: 3/10/13/31/103/391

Setting and addressing: Martin P3™ System controller or RDM-compliant controller

Control resolution: 16-bit (P3) or 8-bit (DMX) control of each color

Color and intensity calibration: Pixel-level

DMX compliance: USITT DMX512-A

RDM compliance: ANSI/ESTA E1.20

Firmware update: Via Martin P3™ System Controller

Control/User Interface

Device status: Multi-color visual indication

Device test and reset: Magnetic pushbutton to call up local test patterns and reset device

Optics

Options:

Clear Front

Flat Diffuser

Round Diffuser

Square Diffuser

Linear Asymmetric Lens

Minimum LED lifetime: 50 000 hours (to >70% luminous output)*

**Figure obtained under manufacturer's test conditions:*

Photometric Data

Color resolution: 16 bits per color (48 bit per pixel)

Viewing angle: 120° x 120°

Pixels per meter: 100

Pitch (pixel center-to-center): 10.00 mm

Luminous intensity, calibrated mode: 250 cd per meter*

Total output, calibrated mode: 750 lumens per meter*

Total output, calibrated mode: 8 333 nits (modules spaced 30 mm center-to-center)*

**Preliminary data, figures are approximate:*

Video Processing

Brightness control

Gamma correction and control

Color temperature control

Color space control

Calibration processing

Synchronization

Signal Protocol

P3 (via Martin P3™ PowerPort) or DMX

Construction

Base: Extruded aluminum profile

Color: Alu Grey (customized colors available on project basis)

Protection rating: IP66

Impact resistance: IK05

RoHS compliant

Installation

Orientation: Any

Mounting: Slot for locking nuts on back of profile (M6) and/or installation mounting profile

Connections

Power and data input: 6-pin custom (BBD) IP66-rated

Power and data thru: 6-pin custom (BBD) IP66-rated

Hot plugging compatible

Electrical

Nominal input voltage: 48 VDC +/- 4%

Power supply options: Martin P3™ PowerPort 1500, P3™ PowerPort 1000 IP, Tripix™

Power IP66 or generic 48 VDC PSU

Max. total power consumption: : 33 W per meter (at max. intensity, full white)

Thermal

Cooling: Convection

Maximum ambient temperature (Ta max.): 55° C (131° F)

Minimum ambient temperature (Ta min.): -20° C (-4° F)

Total heat dissipation (calculated, +/- 10%): 115 BTU/hr per meter

Approvals

EU safety: EN 60950-1, EN 60950-22

EU EMC: EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3

US safety: UL 60950-1, UL 60950-22

US EMC: FCC Part 15 Class A

Canadian safety: CSA C22.2 No. 60950-1, No. 60950-22

Canadian EMC: ICES-003 Class A

Australia/NZ: RCM

Accessories

Magnetic Test Tool, set of 10: P/N 91610139

Mounting hardware

Exterior PixLine™ 10 Mounting Profile, 320 mm (12.6 in.), aluminum: P/N 91611620

Exterior PixLine™ 10 Mounting Profile, 1280 mm (50.4 in.), aluminum: P/N 91611610

Exterior PixLine™ Mounting Profile Locks, set of 10: P/N 91611725

Cables

Power + Data Input Cable, 4-pin male XLR (for P3 PowerPort 1500) to fem. BBD, 0.25 m (0.9 ft.): P/N 11840257

Power + Data Input Cable, 5-pin male XLR + wire tails (for PSU) to female BBD, 0.25 m (0.9 ft.): P/N 11840276

Power + Data Input Cable, 5-pin male XLR + male Tripix IP66 PSU to fem. BBD, 0.25 m (0.9 ft.): P/N 11840275

Power + Data Extension Cable, Installation type CMX, BBD-BBD 1 m (3.3 ft.): P/N 11840270

Power + Data Extension Cable, Installation type CMX, BBD-BBD, 2.5 m (8.2 ft.): P/N 11840271

Power + Data Extension Cable, Installation type CMX, BBD-BBD, 5 m (16.4 ft.): P/N 11840272

Power + Data Extension Cable, Installation type CMX, BBD-BBD, 10 m (32.9 ft.): P/N 11840273
Power + Data Extension Cable, Installation type CMX, BBD-BBD, 25 m (82.1 ft.): P/N 11840274
Power + Data Extension Cable, Installation type CMX, without connectors, 100 m (328.1 ft.): P/N 11840278
Blanking caps for unused female BBD connectors, set of 10: P/N 62409876
DMX Leadout Adapter, male BBD to 5-pin female XLR, 0.25 m (0.9 ft.): P/N 11840258

Connectors

Power + Data Cable Connector, BBD, male: P/N 91611750
Power + Data Cable Connector, BBD, female: P/N 91611751

Related Items

Martin P3™ PowerPort 1500: P/N 90721040
Martin P3™ PowerPort 1000 IP Installation: P/N 90721080
Martin™ IP66 PSU 240 W external power supply unit: P/N 90760330
Martin P3-050™ System Controller: P/N 90721090
Martin P3-100™ System Controller: P/N 90721010
Martin P3-150™ System Controller: P/N 90721015
Martin P3-200™ System Controller: P/N 90721020
Martin P3-300™ System Controller: P/N 90721060
Martin P3-PC™ System Controller: P/N 90721030

Ordering Information

Exterior PixLine™ 10 RGB, 320 mm, Clear Front, Aluminum: P/N 90356895
Exterior PixLine™ 10 RGB, 1280 mm, Clear Front, Aluminum: P/N 90356890
Exterior PixLine™ 10 RGB, 320 mm, Diffuser Front, Aluminum: P/N 90356885
Exterior PixLine™ 10 RGB, 1280 mm, Diffuser Front, Aluminum: P/N 90356880
Exterior PixLine™ 10 RGB, 320 mm, Round Diffuser Front, Aluminum: P/N 90356875
Exterior PixLine™ 10 RGB, 1280 mm, Round Diffuser Front, Aluminum: P/N 90356870
Exterior PixLine™ 10 RGB, 320 mm, Square Diffuser Front, Aluminum: P/N 90356865
Exterior PixLine™ 10 RGB, 1280 mm, Square Diffuser Front, Aluminum: P/N 90356860
Exterior PixLine™ 10 RGB, 320 mm, Asymmetric Lens Left, Aluminum: P/N 90356855
Exterior PixLine™ 10 RGB, 1280 mm, Asymmetric Lens Left, Aluminum: P/N 90356850
Exterior PixLine™ 10 RGB, 320 mm, Asymmetric Lens Right, Aluminum: P/N 90356845
Exterior PixLine™ 10 RGB, 1280 mm, Asymmetric Lens Right, Aluminum: P/N 90356840
For asymmetric lens models, Left or Right = direction of light output when looking from male to female connector

