




Exterior PixLine 40

The Exterior PixLine 40 is a linear LED video fixture for media facades and creative installations. The Exterior PixLine 40 can be combined with a wide variety of lenses and diffusers for the right look for every application. The Exterior PixLine 40 is driven by the Martin P3 System Controller family for easy setup and video display, and it is also backwards compatible with DMX. The fixtures can be fully customized in terms of length and color to match every installation requirement, while the power source is hidden.

GALLERY



Wide range of pixel pitch, lens and diffuser options for the flexibility of look

Fully outdoor-rated and customizable in terms of length and color

Easy setup and cabling for clean installation

FEATURES

- 40 mm pixel pitch
- 62 cd per meter calibrated
- 40 lumen per foot calibrated
- High-quality 16-bit per color image processing technology
- Pixel-level brightness and color calibration for optimal image quality
- P3/DMX controllable (automatic protocol detection)
- Intuitive mapping and addressing via P3 System Controller
- Combined power/data input (single cable for power and data input)
- Supported by integrated power and data processor (P3 PowerPort 1500 or P3 PowerPort 1000 IP) and simple cabling system
- Available in standard length of 1280 mm and 320 mm (customized lengths also available)

TECHNICAL SPECIFICATIONS

Physical

Length: Available in 310 mm and 1270 mm length versions*

**Fixtures must be installed with a 10 mm gap to allow for thermal expansion*

Custom lengths are available to special order on project basis as follows:

Minimum custom length: 320 mm (12.6 in.)

Maximum custom length: 2000 mm (78.8 in.)

Custom length increments: 40 mm (1.6 in.)

NB: To allow for thermal expansion, fixtures are 10 mm shorter than the nominal lengths given above

Width: 27 mm (1.1 in.)

Height with flat diffuser / clear front: 32 mm (1.3 in.)

Height with flat diffuser / clear front in mounting profile: 74 mm (3.0 in.)

Height with asymmetric wallwasher lens: 42 mm (1.7 in.)

Height with asymmetric wallwasher lens in mounting profile: 84 mm (3.4 in.)

Height with round diffuser: 42 mm (1.7 in.)

Height with round diffuser in mounting profile: 84 mm (3.4 in.)

Weight: 1.2 kg / m (0.9 lbs. per foot)

Control and Programming

Control options: Martin P3™ System Controller via Martin P3™ PowerPort 1500 / Martin P3™ PowerPort 1000 IP, and/or DMX

Protocol detection: Automatic

Control modes: RGB, basic, segment and pixel-level

Setting and addressing: Martin P3™ System Controller or RDM-compliant controller
Control resolution: 16-bit (P3) or 8-bit (DMX) control of each color
Color and intensity calibration: Pixel-level
DMX compliance: USITT DMX512-A
RDM compliance: ANSI/ESTA E1.20
Firmware update: Via Martin P3™ System Controller
DMX channels: 3/10/13/31/31/103

Control/User Interface
Device status: Multi-color visual indication
Device test and reset: Magnetic pushbutton to call up local test patterns and reset device

Optics

Options

Clear Front

Flat Diffuser

Round Diffuser

Square Diffuser

Linear Asymmetric Lens

Minimum LED lifetime: 50 000 hours (to >70% luminous output)*

**Figure obtained under manufacturer's test conditions:*

Photometric Data

Color resolution: 16 bits per color (48 bit per pixel)

Viewing angle: 120° x 120°

Pixels per meter: 25

Pitch (pixel center-to-center): 40.00 mm

Luminous intensity, calibrated mode: 62 cd per meter*

Total output, calibrated mode: 187 lumens per meter*

Total output, calibrated mode: 2 083 nits (modules spaced 30 mm center-to-center)*

**Preliminary data, figures are approximate:*

Video Processing

Brightness control

Gamma correction and control

Color temperature control

Color space control

Calibration processing

Synchronization

Signal Protocol

P3 (via Martin P3™ PowerPort) or DMX

Construction

Base: Extruded aluminum profile

Color: Clear anodized (customized colors available on project basis)

Protection rating: IP66

Impact resistance: IK05

RoHS compliant

Installation

Orientation: Any

Mounting: Slot for locking nuts on back of profile (M6) and/or installation mounting profile

Connections

Power and data input: 6-pin custom (BBD) IP66-rated

Power and data thru: 6-pin custom (BBD) IP66-rated

Hot plugging compatible

Electrical

Nominal input voltage: 48 VDC +/- 4%

Power supply options: Martin P3™ PowerPort 1500, Martin P3™ PowerPort 1000 IP or generic 48 VDC PSU

Max. total power consumption: 8.5 W per meter (at max. intensity, full white)

Thermal

Cooling: Convection

Maximum ambient temperature (Ta max.): 55° C (131° F)

Minimum ambient temperature (Ta min.): -20° C (-4° F)

Total heat dissipation (calculated, +/- 10%): 30 BTU/hr per meter

Approvals

EU safety: EN 60950-1, EN 60950-22

EU EMC: EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3

US safety: UL 60950-1, UL 60950-22

US EMC: FCC Part 15 Class A

Canadian safety: CSA C22.2 No. 60950-1, No. 60950-22

Canadian EMC: ICES-003 Class A

Australia/NZ: RCM

Accessories

Magnetic Test Tool, set of 10: P/N 61610139

Mounting hardware

Exterior PixLine™ 40 Mounting Profile, 310 mm (12.2 in.), aluminum: P/N 91611700

Exterior PixLine™ 40 Mounting Profile, 1270 mm (50.0 in.), aluminum: P/N 91611710

Exterior PixLine™ Mounting Profile Locks, set of 10: P/N 91611725

Cables

Power + Data Input Cable, 4-pin male XLR (for P3 PowerPort 1500) to fem. BBD, 0.25 m (0.9 ft.): P/N 11840257

Power + Data Input Cable, 5-pin male XLR + wire tails (for PSU) to female BBD, 0.25 m (0.9 ft.): P/N 11840276

Power + Data Input Cable, 5-pin male XLR + male Triplex IP66 PSU to fem. BBD, 0.25 m (0.9 ft.): P/N 11840275

Power + Data Extension Cable, Installation type CMX, BBD-BBD 1 m (3.3 ft.): P/N 11840270
Power + Data Extension Cable, Installation type CMX, BBD-BBD, 2.5 m (8.2 ft.): P/N 11840271
Power + Data Extension Cable, Installation type CMX, BBD-BBD, 5 m (16.4 ft.): P/N 11840272
Power + Data Extension Cable, Installation type CMX, BBD-BBD, 10 m (32.9 ft.): P/N 11840273
Power + Data Extension Cable, Installation type CMX, BBD-BBD, 25 m (82.1 ft.): P/N 11840274
Power + Data Extension Cable, Installation type CMX, without connectors, 100 m (328.1 ft.): P/N 11840278
Blanking caps for unused female BBD connectors, set of 10: P/N 62409876
DMX Leadout Adapter, male BBD to 5-pin female XLR, 0.25 m (0.9 ft.): P/N 11840258

Connectors

Power + Data Cable Connector, BBD, male: P/N 91611750
Power + Data Cable Connector, BBD, female: P/N 91611751

Related Items

Martin P3™ PowerPort 1500: P/N 90721040
Martin P3™ PowerPort 1000 IP Installation: P/N 90721080
Martin™ IP66 PSU 240 W external power supply unit: P/N 90760330
Martin P3-050™ System Controller: P/N 90721090
Martin P3-100™ System Controller: P/N 90721010
Martin P3-150™ System Controller: P/N 90721015
Martin P3-200™ System Controller: P/N 90721020
Martin P3-300™ System Controller: P/N 90721060
Martin P3-PC™ System Controller: P/N 90721030

Ordering Information

Exterior PixLine™ 40
Exterior PixLine™ 40 RGB, 310 mm, Clear Front, Aluminum: P/N 90356775
Exterior PixLine™ 40 RGB, 1270 mm, Clear Front, Aluminum: P/N 90356770
Exterior PixLine™ 40 RGB, 310 mm, Diffuser Front, Aluminum: P/N 90356765
Exterior PixLine™ 40 RGB, 1270 mm, Diffuser Front, Aluminum: P/N 90356760
Exterior PixLine™ 40 RGB, 310 mm, Round Diffuser Front, Aluminum: P/N 90356755
Exterior PixLine™ 40 RGB, 1270 mm, Round Diffuser Front, Aluminum: P/N 90356750
Exterior PixLine™ 40 RGB, 310 mm, Square Diffuser Front, Aluminum: P/N 90356745
Exterior PixLine™ 40 RGB, 1270 mm, Square Diffuser Front, Aluminum: P/N 90356740
Exterior PixLine™ 40 RGB, 310 mm, Asymmetric Lens Left, Aluminum: P/N 90356735
Exterior PixLine™ 40 RGB, 1270 mm, Asymmetric Lens Left, Aluminum: P/N 90356730
Exterior PixLine™ 40 RGB, 310 mm, Asymmetric Lens Right, Aluminum: P/N 90356725
Exterior PixLine™ 40 RGB, 1270 mm, Asymmetric Lens Right, Aluminum: P/N 90356720
For asymmetric lens models, Left or Right = direction of light output when looking from male to female connector

