

# F 10XR

## 10-CHANNEL MIXING CONSOLE WITH MULTI-FX & RECORDING

### DESCRIPTION

The F 10XR features 4 mic preamp inputs, 2 mono line inputs, 4 stereo line inputs plus multi-FX and recording via USB port, with balanced main output (stereo XLR + TRS) and 2 single control compressors. The mono channels are provided with 3-band EQ and stereo channels with 2-band. The mixer features 16 PRO DSP internal FX presets and an aux send (post fader) with rotary knob control.



### FEATURES

- 4 Mic preamp inputs, 2 mono line inputs
- 4 stereo line inputs
- PRO DSP FX onboard with 16 presets
- Stereo recording and playback via USB port
- 2 single control compressors
- Balanced main output +28 dB (Stereo XLR + TRS)
- 1 aux/FX (post)
- Sturdy metal chassis
- External universal power supply
- Designed and engineered in Italy

## TECHNICAL SPECIFICATIONS

|                           |                                                   |                         |
|---------------------------|---------------------------------------------------|-------------------------|
| Electronic specifications | Frequency Response:<br>THD+N, 20dB gain, 0dBu out | 20 Hz ÷ 20 kHz<br><0,02 |
|---------------------------|---------------------------------------------------|-------------------------|

|        |                                    |                |
|--------|------------------------------------|----------------|
| Inputs | Mic:                               | 4              |
|        | Gain Range:                        | 0 dB ÷ -50 dB  |
|        | Mic Inputs Impedance:              | 14 kohm        |
|        | Low Cut:                           | 80 Hz          |
|        | Phantom Power +48V:                | Yes            |
|        | Mono Line:                         | 2              |
|        | Gain Selection:                    | 20 dB ÷ -30 dB |
|        | Line Input Impedance:              | 21 kohm        |
|        | Stereo Line:                       | 4              |
|        | Gain Selection:                    | 20 dB ÷ -30 dB |
|        | Stereo Line Input Impedance (kOhm) | 15 kohm        |

|         |               |     |
|---------|---------------|-----|
| Outputs | Main MIX:     | 1   |
|         | Control Room: | Yes |
|         | FX Send:      | 1   |
|         | AUX Output:   | 1   |
|         | Phones:       | 1   |

|                        |                             |         |
|------------------------|-----------------------------|---------|
| Outputs specifications | Main Out Level:             | 28 dBu  |
|                        | Aux Out Level:              | 28 dBu  |
|                        | Phones Out impedance (ohm): | 150 ohm |

|             |                  |                                                 |
|-------------|------------------|-------------------------------------------------|
| Compressors | RCF Compressors: | n° 2 Single Control compressors on channels 1&2 |
|-------------|------------------|-------------------------------------------------|

|    |                    |                                                                                                       |
|----|--------------------|-------------------------------------------------------------------------------------------------------|
| EQ | Input Channels EQ: | 2 Shelving / 1 Generic                                                                                |
|    | Description:       | High: +/-15 dB @ 10 kHz Shelving<br>Mid: +/-15 dB @ 1,250 kHz Bell<br>Low: +/-15 dB @ 100 Hz Shelving |

|                 |          |   |
|-----------------|----------|---|
| Auxiliary sends | FX POST: | 1 |
|-----------------|----------|---|

|                  |               |   |
|------------------|---------------|---|
| Internal Effects | Send Effects: | 1 |
|------------------|---------------|---|

|                           |                          |                       |
|---------------------------|--------------------------|-----------------------|
| USB audio                 | Type:                    | B                     |
|                           | Play trk:                | 2                     |
|                           | Rec trk:                 | 2                     |
|                           | Supported Sample Rate:   | 44.1, 48.0            |
| Other features            | Footswitch:              | Yes                   |
| Electrical specifications | Power supply:            | External              |
|                           | Voltage requirements:    | 100 V - 240 V         |
|                           | Power consumption (MAX): | 18 W                  |
| Standard compliance       | CE marking:              | Yes                   |
| Physical specifications   | Cabinet/Case Material:   | Metal                 |
|                           | Color:                   | Black                 |
| Size                      | Height:                  | 82 mm / 3.23 inches   |
|                           | Width:                   | 294 mm / 11.57 inches |
|                           | Depth:                   | 275 mm / 10.83 inches |
|                           | Weight:                  | 2.8 kg / 6.17 lbs     |
| Shipping informations     | Package Height:          | 130 mm / 5.12 inches  |
|                           | Package Width:           | 400 mm / 15.75 inches |
|                           | Package Depth:           | 345 mm / 13.58 inches |
|                           | Package Weight:          | 3.8 kg / 8.38 lbs     |

## PART NUMBER

- 17140089

F 10XR

EAN 8024530016142

