

Intimidator Spot 260X

- Compact moving head designed for mobile events
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- New home position allows for smoother programming
- ¼-turn hanging bracket allows for quick removal when needed
- Project crisp gobos from nearly any distance with the motorized focus
- Manual zoom for short or long throw applications
- 3-facet prism splits the beam and covers a larger area
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full color LCD display
- Link up to 4 fixtures to create eye-catching, synchronized shows in Automated or Sound mode
- powerCON®-compatible power input/output connections saves setup time
- Fits best in the CHS-2XX VIP Gear Bag

Specifications

- DMX Channels: 8 or 14
- DMX Connectors: 3-pin XLR
- Pan and Tilt: 540°/234°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/234°, 180°, 90° tilt
- Colors: 8 + white, split colors, continuous scroll at variable speeds
- Gobos: 7 + open (6 metal + 1 glass), rotating, interchangeable, slot-n-lock, continuous scroll at variable
- Gobo Size: 24 mm outside, 20 mm image, 1.1 mm max thickness
- Light Source: 1 LED (cool white) 75 W, (3.3 A), 50,000 hours life expectancy
- Prism: 3-facet round, static
- Strobe Rate: 0 to 20Hz
- Zoom angle (manual): 12° to 17°
- Illuminance (12°) : 17,458 lux @ 2 m
- Illuminance (17°) : 12,848 lux @ 2 m
- Color Temperature: 15,000 K
- Power Linking: 7 units @ 120 V; 11 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 124 W, 1.8 A @ 120 V, 60 Hz
- Power and Current: 128 W, 1 A @ 230 V, 50 Hz
- Bracket Mounting Hole: 13 mm
- Optional Controllers: RFC, RFC-XL
- Approvals : CE, UKCA, RoHS



- Weight: 12.2 lb (5.6 kg)
- Size: 9.1 x 6.4 x 13.8 in (232 x 163 x 351 mm)

