

Intimidator Spot 360X

- Compact moving head designed for mobile events
- Built-in RF receiver for wireless control using the RFC or RFC XL optional remotes
- New home position allows for smoother programming
- Dual rotating prisms split the beam for great effects and cover a larger area
- Manual zoom for short or long throw applications
- ¼-turn hanging bracket allows for single or dual clamp mounting options
- Project crisp gobos from nearly any distance with the motorized focus
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- powerCON®-compatible power input/output connections saves setup time
- Fits best in the CHS-360 VIP carry bag or the Intimidator Road Case

Specifications

- DMX Channels: 8 or 14
- DMX Connectors: 3-pin XLR
- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors: 8 + white, split colors, continuous scroll at variable speeds
- Gobos: 7 + open (6 metal + 1 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Gobo Size: 24 mm outside, 20 mm image, 1.1 mm max thickness
- Prism: 5-facet linear, bi-directional at variable speeds
- Prism: 3-facet round, bi-directional at variable speeds
- Light Source: 1 LED (cool white) 100 W, (4.3 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 20 Hz
- Zoom angle (manual): 12° to 17°
- Illuminance (12°) : 41,601 lux @ 2 m
- Illuminance (17°) : 22,534 lux @ 2 m
- Lumens : 3,967
- Color Temperature: 15,000 K
- Power Linking: 5 units @ 120 V; 8 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 217 W, 2.6 A @ 120 V, 60 Hz
- Power and Current: 211 W, 1.5 A @ 230 V, 50 Hz
- Optional Controllers: RFC, RFC-XL
- Approvals : CE, UKCA, RoHS, MET



- Weight: 25 lb (11.4 kg)
- Size: 12.7 x 8.7 x 16.7 in (322 x 220 x 423 mm)

