

# Maverick Storm 2 Profile



- Battery backup display with auto-rotate depending on fixture orientation

## SPECIFICATIONS

### OPTICAL

- Light Source: 1 LEDs (CW) 580 W, (4.2 A), 7500 K, 50,000 hours life expectancy
- Color Temperature (at full): 7268 K
- CRI: 71.3
- CRI with CRI Filter: 89.8
- Front Lens Diameter: 127 mm
- Beam Angle: 5.5° to 41.8°
- Field Angle: 7.8° to 52.6°
- Cutoff Angle 8.3° to 56.5°
- Zoom Range: 5.5° to 56.5°
- Lumens – Source: 35,000
- Lumens – Output: 28,000
- Illuminance (6.8°) 65,964 lux @ 5 m
- Illuminance (54.8°) 2,588 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 4,000 Hz, 6,000 Hz, 15,000 Hz

## FEATURES

- Fully featured, compact and lightweight IP65 580 W LED yoke profile fixture including CMY + CTO color mixing, a 4-blade framing shutter system with rotation, a color wheel, 10:1 zoom, a 5-facet prism wheel, 1 rotating and 1 static gobo wheel, integrated sun shield
- 16-bit dimming of master dimmer for smooth control of fades
- Variable CMY + CTO color mixing system to create a wide pallet of colors
- CRI and CTB filters on color wheel for added flexibility
- One rotating, indexing and interchangeable slot and lock gobo wheel
- One rotating static gobo wheel
- DMX, WDMX, sACN, and Art-Net for full flexibility of control options
- RDM control over DMX for fixture reporting
- 5.5° to 56.5° zoom range for variable beam sizes
- Iris, 5-facet prism and frost for beam control
- True 1 compatible power input
- Integrated sun shield for protecting the optical path from sunlight when the fixture is off
- Three setup menu presets and preset sync for cross loading to multiple like fixtures for easy shop setup
- USB slot for software uploads

### DYNAMIC EFFECTS

- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors: 7 (including CRI and CTB filters) + white, split colors, continuous scroll at variable speeds
- Colors: CMY flags, CTO flag
- Gobos (1): 7 + open (glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Gobos (2): 9 + open (glass), continuous scroll at variable speeds
- Gobo Size: Gobo Wheel 1 (rotating): 25.5 mm (outside), 18 mm (image), 1.1 mm (max. thickness)
- Framing Shutters: 4 Blades, each with dual axis movement, Full blackout.
- Framing Shutter rotation: +/- 60° rotation.
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Zoom: Motorized
- Focus: Motorized
- Frost: Motorized
- Iris: Motorized
- Prism: 5 Facets, motorized, rotating
- Strobe Rate: 0 to 20 Hz
- Move-in-Black: Yes
- Dim Curves: 4

## CONSTRUCTION/PHYSICAL

- Dimensions: 9.92 x 15.28 x 27.52 in (252 x 388 x 699 mm)
- Weight: 67.0 lb (30.4 kg)
- Exterior Color: Black
- Housing Material: Aluminum diecast, High-impact flame-retardant polymer, Steel

## CONNECTIONS

- Power Connection: Seetronic Powerkon IP65
- Power Input/Output: Seetronic Powerkon IP65
- Data Connectors: 5-pin IP rated XLR, Neutrik IP rated RJ45 Connectors in/out
- Cable Length (power): 5 ft (1.5 m)

## CONTROL

- Control Protocol: Art-Net, DMX, RDM, W-DMX, sACN
- DMX Channels: 32 or 48
- Art-Net Channels: 32 or 48
- Modes/Personalities: 2 personalities (32, 48)

## ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 800 W, 6.82 A @ 120 V, 60 Hz
- Power and Current: 779 W, 3.77 A @ 208 V, 60 Hz
- Power and Current: 763 W, 3.41 A @ 230 V, 50 Hz
- Breaker Size: F15 A, 250 V
- 

## WHAT'S INCLUDED

- Maverick Storm 2 Profile
- Seetronic Powerkon IP65 power cord to Edison
- Omega bracket with mounting hardware

## OPTIONAL ACCESSORIES

- Professional Clamps : CTC-50HC, CTC-50HCN
- Safety Cable: SC-07
- DMX Cables
- IP Rated Seetronic® Powerkon Extensions