

## **S 29 WP**

### HIGH-POWER WEATHERPROOF SUBWOOFER



### Description

S 29 WP is a high-power dual 19" cone subwoofer suitable for high-powered outdoor applications. The bass-reflex design ensures an efficient acoustic response down to 25 Hz. The high-quality plywood cabinet is finished with a black, heavy-duty polyurea coating and protected by a powder-coated metal grille. An M20 pole mount adapter is provided on top of the cabinet, with handles on both sides. The enclosure can be ground-stacked and cardioid-arrayable for improved rear rejection. For enhanced weather resistance, the WP model features an acoustically transparent, water-repellent fabric discreetly embedded within the grille assembly and IP67 Amphenol Ecomate power connectors.

#### Features

- > Up to 3000 W power handling
- > 143 dB max SPL
- > 25 ÷ 200 Hz frequency range
- > 2 x 19" HyperVented Neodymium Woofer with 4" v.c.
- > High-quality polyurea-coated multi-ply cabinet
- > Steel grille with water-repellent protection
- > Integrated M20 threaded pole mount on top
- > 2 x Amphenol eco|mate IP 67 connectors

Part Number

13100108 S 29 WP


EAN 8024530022334




# **S 29 WP**

### HIGH-POWER WEATHERPROOF SUBWOOFER

### Line Art 2D





25 Hz ÷ 200 Hz

12000 W PEAK

CE compliant

XPS 16K, XPS 16KD

2 x 19" neo, 4.0" v.c

143 dB

4 ohm

3000 W

Full Range

### **TECHNICAL SPECIFICATIONS**

**Acoustical specifications** 

Frequency Response (-10dB)

Max SPL @ 1m

**Power section** 

Amplification

Nominal Impedance Power Handling Peak Power Handling

Recommended Amplifiers

**Transducers** 

Woofer

Input/Output section

Amphenol eco/mat IP 67 Input connectors Output connectors Amphenol eco/mat IP 67

Standard compliance **Physical specifications**  Safety agency

Cabinet/Case Material Plywood Handles

Grille

2 side Pole mount/Cap M20 thread Steel grille with water-repellent protection

Size / Weight Height Width

534 mm / 21.02 inches 1300 mm / 51.18 inches 730 mm / 28.74 inches Depth Weight 85 kg / 187.39 lbs

**Technical Specifications** Page 2 of 2