

# Shocker Panel 480

- Punchy, single-zone blinder with cool white SMD LEDs
- Rugged housing makes it ideal for mobile applications
- Trigger eye-catching strobe effects via the built-in display, DMX, or with the optional IRC6 remote
- powerCON®-compatible power input/output connections for power linking
- Save time running cables and extension cords by power linking multiple units
- Easily transports in the optional CHS-25 VIP gear bag



## Specifications

- DMX Channels: 4
- DMX Connectors: 3-pin XLR
- Light Source: 480 SMD LEDs (cool white) 0.7 W (236 mA), 50,000 hours life expectancy
- Strobe Rate: 0 to 28 Hz
- PWM Frequency: 4,000 Hz
- Beam Angle: 111°
- Field Angle: 155°
- Illuminance: 1,348 lux @ 2 m
- Lumens: 14,974
- Color Temperature: 7000 K
- Power Linking: 5 units @ 120 V; 9 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 208 W, 2.7 A @ 120 V, 60 Hz
- Power and Current: 200 W, 1.5 A @ 230 V, 50 Hz
- Bracket Mounting Hole: 13 mm
- Weight: 9.4 lb (4.3 kg)
- Size: 13.1 x 4.5 x 6.7 in (332 x 115 x 170 mm)
- Optional Controllers: IRC6
- Approvals: CE, UKCA

