

STRIKE Array 1

FEATURES

- Intense, stacking blinder/strobe rated IP65 for all-weather use
- Remote driver unit with automatic addressing of up to 8 pods for clean installations.
- Heads are removable from the frame and can be mounted in standard (included) yoke for a more traditional look.
- Emulated "red shift" to mimic incandescent fixtures perfectly.
- Manual pan (or tilt, depending on mount orientation) of each head to allow for directional adjustment of light output.
- Innovative interlocking system to connect multiple fixtures together.



SPECIFICATIONS

OPTICAL

- Light Source (Single Pod): 48 LED (WW) 1.33 W, (1.1 A), 2700 K, 50,000 hours life expectancy
- Light Source (Single Pod): 5 LED (Amber) 1.92 W, (.770 A), 50,000 hours life expectancy
- Color Temperature (at full): 2657 K
- CRI: 83.9
- Beam Angle: 62.8°
- Field Angle: 104.5°
- Lumens (Single Pod): 4,353 lm @ 5 m
- Illuminance (total) (Single Pod): 153 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 25,000 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Strobe Rate: 0 to 25 Hz
- Dim Modes: 4
- Built-in Automated Programs: Yes

CONSTRUCTION / PHYSICAL

- Dimensions: 8.19 x 8.62 x 4.57 in (208 x 219 x 116 mm) (Single Unit with Bracket)
- Dimensions: 7.48 x 7.48 x 4.57 in (190 x 190 x 116 mm) (Single Unit with Frame)
- Dimensions: 10.87 x 9.06 x 4.57 in (276 x 230 x 116 mm) (Single Unit with Frame and Bracket)
- Dimensions: 7.375 x 4.00 x 7.375 in (186.87 x 101.6 x 186.87 mm) (Control Box)
- Weight: 3.2 lbs (1.5 kg) (Single Unit with Bracket)
- Weight: 6.6 lbs (3.0 kg) (Single Unit with Frame)
- Weight: 7.6 lbs (3.5 kg) (Single Unit with Frame and Bracket)
- Weight: 6.4 lbs (2.9 kg) (Control Box)
- Exterior Color: Black
- Housing Material: Aluminum die-cast

CONNECTIONS

- Power Connection: Edison (Local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Power Output: Seetronic Powerkon IP65
- Device Outputs (4): 4-pin XLR

- Data Connectors: 5-pin IP65 XLR, Seetronic Etherkon IP65
- Cable Length (power): 5 ft (1.5 m)
- Software Connection: USB

CONTROL

- Control Protocol: DMX, RDM, ArtNet, sACN
- DMX Channels: 1,2,5,4P-5CH,4P-14CH,4P-23CH,4P-26CH,8P-9CH,8P-26CH,8P-43,8P-46CH

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current (4 PODS): 253 W, 2.13 A @ 120 V, 60 Hz
- Power and Current (4 PODS): 248 W, 1.21 A @ 208 V, 60 Hz
- Power and Current (4 PODS): 248 W, 1.09 A @ 230 V, 50 Hz
- Power Linking: 2 units @ 120 V; 5 units @ 208 V; 5 units @ 230 V
- Power Linking: 5 units @ 120 V; 9 units @ 208 V; 11 units @ 230 V
- Power and Current (8 PODS): 509 W, 4.22 A @ 120 V, 60 Hz
- Power and Current (8 PODS): 494 W, 2.38 A @ 208 V, 60 Hz
- Power and Current (8 PODS): 490 W, 2.14 A @ 230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET, FCC
- IP Rating: IP65, temporary outdoor/wet use, with pressure equalizing M6 GORE valve
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

WHAT'S INCLUDED

- 4pc Strike Array 1, mounted in the Square Frame with Yokes
- 4pc linking cables (1m)
- 1pc Seetronic Powerkon IP65
- 1pc driver
- 4pc "head only yokes"
- 5pc Omega Bracket

OPTIONAL ACCESSORIES

- Professional Clamps: CTC-50HC, CTC-50HCN
- Safety Cable: SC-07
- IP Rated Seetronic® Powerkon Extensions
- IP Rated DMX cables
- IP Rated EtherCon Cables
- UPLOAD 03 software uploader