

# Swarm Wash FX ILS

- 4-in-1 LED light that combines an RGBAW rotating derby, RGB+UV wash, red/green laser, and a ring of white SMD strobes
- ILS compatibility for use in the ILS ecosystem
- D-Fi USB compatibility for wireless Master/Slave, or DMX control
- Access built-in automated programs via IRC6 remote, Master/Slave or DMX
- Red and green laser beams project thousands of beams for maximum coverage
- Generate complex looks easily with built-in, eye-catching automatic and sound-activated programs
- Save time running extension cords by power linking multiple unit
- Fits best inside the CHS-40 VIP gear bag

## Specifications

- DMX Channels: 2 or 18
- DMX Connectors: 3- pin XLR
- Light Source (Swarm): 5 LEDs (1 red, 1 green, 1 blue, 1 amber, 1 white) 2 W (650 mA) 50,000 hours life expectancy
- Light Source (Wash): 8 LEDs (quad-color RGB+UV) 1.5 W, (600 mA), 50,000 hours life expectancy
- Light Source (Strobe) 12 LEDs (white) 1 W, (300 mA), 50,000 hours life expectancy
- Light Source (Laser): 650 nm/100 mW (red) laser diode, 520 nm/30 mW (green) laser diode
- Strobe Rate: 0 to 20 Hz
- Coverage Angle (laser): 82°
- Coverage Angle (swarm): 65°
- Coverage Angle (strobe): 71°
- Coverage Angle (wash): 46°
- Power Linking: 11 units @ 120 V; 20 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 51 W, 0.7 A @ 120 V, 60 Hz
- Power and Current: 50 W, 0.4 A @ 230 V, 50 Hz
- Optional Controllers: IRC6
- Classified per EN/IEC 60825-1:2014
- Complies with FDA performance standards for laser products except for deviations pursuant to Laser Notice No. 56, dated May 8, 2019
- Approvals: CE, FDA, RoHS, UKCA



- Weight: 9.5 lb (4.3 kg)
- Size: 13.1 x 13 x 9.4 in (335 x 332 x 241 mm)

