

tarm 25 OUTDOOR

Outdoor laser, perfectly suitable for fixed installations for advertising, mappings or any kind of graphics projections. The high quality beam with uniform beam profile, due to the full equipment with the high performance RSL modules of the second generation, combined with the fast scanning and upgrade option to CT-6210, makes the tarm 25 OUTDOOR an awesome projection unit.

IP65 waterproof laser system, suitable for outdoor use and fixed installations.



- IP65 waterproof housing
- 24'500 mW guaranteed power
- Complex graphics capable - 45kpps @ 8° ILDA scanners – upgradable to 60kpps
- Extremely sharp intense beams - low divergence of <0.8 mrad
- Integrated powerful mainboard with advanced configuration features (geo-correction, zone setup, color balancing, etc.) and DAC feature
- Control screen (internal) for convenient mode selection
- **Laser Artists' choice**
- **Lighting Designers' choice**

ShowNET mainboard as standard:

- Various control options: **ILDA, Professional DMX and ArtNET** (two modes), **LAN** (computer control, integrated DAC), **Stand-Alone Operation, ILDA Streaming Receiver, Master-Slave**
- Create **custom content**, store it inside the laser and play it back in different modes
- **Free laser show control software** included

TECHNICAL DETAILS

Guaranteed Power at aperture	24'500 mW	Laser Source	RSL modules
Power Red	7'500 mW / 637 nm	IP rating	IP65
Power Green	12'000 mW / 525 nm	Basic Patterns	over 120 (layers, tunnels, fences, waves, etc.)
Power Blue	10'000 mW / 455 nm	Accessories	Incl. power cable, manual, E-Stop, interlock connector, full version Showeditor software license included
Beam Specifications	ca. 5.0 mm / <0.8 mrad	Power Supply	85 V - 250 V / AC
Scanner	45kpps @ 8° ILDA; optional CT-6210 with LAS Turboscan: 60 kpps@8° ILDA, max. 60°	Power Consumption	450 W
Max. Scan Angle	50°	Dimensions	800/370/260 mm
Operation Modes	LAN, ArtNet, ILDA streaming, integrated SD card, stand-alone; integrated intelligent ShowNET laser mainboard with display	Weight	24.0 kg
Laser Class	4	EAN / MPN	7640144996482



AVAILABLE MODIFICATIONS:



*Due to Advanced Optical Correction technology used in our laser systems the optical power of each colour within installed laser module(s) may slightly differ from the specification of respective laser module(s). Divergence FWHM average depending on model.