

DATA SHEET

VIDI 250

4K CONFERENCING CAMERA



The Vidi 250 is a wide angle 4k camera designed for use with conferencing systems. Intended for huddle room or small to medium conferencing rooms, the Vidi 250 has a 120° field of view, allowing everyone in the room to be seen. The Vidi 250 uses auto framing technology to adjust the focus and zoom to keep participants in view. The Vidi 250 can be either display mounted or wall mounted.

FEATURES

- LED indications for camera activity
- Wide angle 120° Field of View
- Auto framing technology to keep participants in frame
- Electronic Pan/Tilt/Zoom with 5x zoom
- Multi-microphone array
- Display mount and wall mount options available
- Covered by Biamp Systems' three-year warranty

ARCHITECTS & ENGINEERS SPECIFICATION

The conferencing camera shall be designed to connect with soft codec conferencing systems. The conferencing camera shall be capable of transmitting video signals of up to 1080p resolution at 30 frames per second. The conferencing camera shall have a 120° field-of-view. The conferencing camera shall include a camera with 5x zoom and electronic pan, tilt, and zoom (ePTZ). The conferencing camera shall include auto framing capabilities that adjusts the ePTZ to intelligently track users. The conferencing camera shall offer simple installation and shall be mountable on a wall or display. The conferencing camera shall be CE marked and compliant with the RoHS directive. Warranty shall be three years. The conferencing camera shall be the Vidi 250.

VIDI 250 SPECIFICATIONS

Camera and Video		Overall Dimensions	
Diagonal Field of View:	120 Degrees	Height:	1.98 inches (50.3 mm)
Image Sensor:	12 Megapixel	Width:	1.97 inches (50 mm)
Focus Distance:	174.1 cm	Depth:	2.76 inches (70 mm)
Lens:	Up to 5x digital zoom	Weight:	160g
Positioning:	Autoframing capability Electronic Pan/Tilt/Zoom	Environmental:	
Camera Indicator:	White/Off	Ambient Operating:	0°C - 40°C
USB Device Video Class (UVC)		Temperature Range:	0°C - 40°C
Supported Video Resolutions:	720p @ 30fps 1080i @ 30fps 1080p @ 30fps 2160p @ 30fps	Humidity:	0% - 95%
Connections		Altitude:	10,000 ft
USB:	USB Type C	Compliance:	CE, UKCA
Power:	USB Type C		

OPTIONAL ACCESSORIES



VMA 200-DM
Side Display Mount



VMA 200-WM
Wall Mount

Biamp is either a trademark or registered trademark of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.