

WELL STX 360 x4



FEATURES

- (4) Pixel-mapping, battery operated, 1.5 meter, IP65 rated LED sticks with 360 degree viewing angle, including (4) mounting stands, (4) hanging eye bolts, (1) IR remote, and (1) charging case
- 16 individual zones of control for pixel mapping effects
- High CRI LEDs for fantastic skin tone rendering
- Simple and complex operational modes
- Built in editable pre-programmed effects that are controllable from the menu and over DMX
- 3, 5, 8, and 12 hour settings for optimizing performance time
- Included accessories for several mounting options
- Included charging flight case for easy transportation and charging of fixtures
- Update software over USB-C connection in flight case (upload all 4 fixtures at once)
- Works in both stand-alone modes as well as under DMX over W-DMX
- Works perfectly with the WELL-COM controller and app

SPECIFICATIONS

OPTICAL

- Light Source: 512 LEDs (256 RGB / 256 WW) SMD 5050, 50,000 hours life expectancy
- Color Temperature (range): 2800 to 8000 K
- Color Temperature (at full): 9670 K
- CRI: 91.9 @ 4000 K
- Beam Angle: 360°
- Field Angle: 360°
- Illuminance (total): 5 lux @ 5 m – 3 hr run time
- Lumens – Output : 1,718 lm – 3 hr run time

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 28 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Built-in Automated Programs: Yes

CONSTRUCTION/PHYSICAL

- Dimensions: 59.09 x 2.75 x 2.75 in (1501 x 70 x 70 mm)
- Dimensions (charging case): 69.8 x 19.5 x 6.4 in (1773 x 495 x 163 mm)
- Weight: 9 lb (4.1 kg)
- Exterior Color: Black
- Housing Material: Aluminum alloy, Plastic

CONNECTIONS

- Power Connection (charging case): Edison (Local) plug to Seetronic Powerkon IP65
- Power Input (charging case): Seetronic Powerkon IP65
- Power Output (charging case): Seetronic Powerkon IP65
- Cable Length power (charging case): 5 ft (1.5 m)

WELL STX 360 x4

CONTROL

- Control Protocol: W-DMX
- DMX Channels: 4, 15, 64 or 67
- Modes/Personalities: 4 personalities

ELECTRICAL

- Input Voltage (charging case): 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking (charging case): 10 units @ 120 V; 10 units @ 208 V; 11 units @ 230 V
- Power and Current (charging case): 160 W, 1.324 A @ 120 V, 60 Hz
- Power and Current (charging case): 264 W, 1.260 A @ 208V, 60 Hz
- Power and Current (charging case): 268 W, 1.188 A @ 230 V, 50 Hz
- Power and Current (charging case): 268 W, 1.124 A @ 240 V, 50 Hz

BATTERY SPECIFICATIONS

- Battery type: Lithium Ion
- Rechargeable: Yes
- Battery Charge Time: 4 hours
- Battery Life: 3,5,8,12 hours
- Battery Power: 18.5 V, 10.05 Ah

CERTIFICATIONS/QUALIFICATIONS

- CE,FCC
- IP Rating: IP65, for temporary outdoor use

WHAT'S INCLUDED

- (4) WELL STX 360
- True 1 style power cord with Edison plug (EU bare end)
- (1) Charging flight case
- (4) tripod stands
- (4) hanging eye bolts
- (1) IR Remote
- Quick Reference Guide