


Specifications

Overview



Connections

Video Input Choice of Multimode or Singlemode
Choice of Optical SDI on ST, OpticalCON DUO
or OpticalCON QUAD
(see ordering information)

Video Output 2 x 12G/6G/3G/HD/SD SDI BNC

Supported Signals

Video Format Support 12G/6G/3G-SDI Level A and B, HD-SDI, SD-SDI
with embedded audio

SMPTE Standards 2082-1, 2082-10, 425 M Level A & B, 424 M,
292 M, 259 M

Physical Specifications

Height 50 mm (1.97 in)

Depth 180 mm (7.08 in)

Width 107 mm (4.21 in)

Weight 1 kg (2.2 lbs)

Alternate Form Factor Also available as a Reversible Module

Environmental Specifications

Relative Humidity 0% to 90% non-condensing

Operating Temperature 0-40 °C

Power Requirements

Power Supply Built-in power supply
PowerCON True1 input
PowerCON True1 output (loop-thru)

Power Consumption 15W

Voltage Range 100-240V, 50-60Hz
(100-120V, 50-60Hz available with PowerCON/
Edison Nema 5-15)

Courtesy Outlet Max 10A, same voltage as input

In the Box

xVision Converter Fiber to 12G-SDI True1
AC Mains to PowerCON True1 cable (1.5m, specify plug type at ordering)

Certifications & Compliance

This device complies with the following international standards

